

ELECTRIC SERIES SCISSOR LIFTS

0607SE(1932SE)

Compliance with ISO/CE/EAC standards

PRODUCT HIGHLIGHTS

- Platform capacity up to 240kg(529lbs)
- Easily passes through standard doors and can access elevators
- The short design of sliding rail makes debris easy to clean
- Bumper rail and indented sliding rail designed for anti-scratch
- DC motor drive, giving a longer runtime



Standard features		
Maintenance-free battery	Automatic braking system	Drive at full height
Proportional control	Emergency lowering system	Forklift pocket and lifting eyes
Bumper rail	Emergency stop at both platform and ground controls	Electrophoresic paint technology
4×2 drive	Fault diagnosis system	Foldable guardrail
Non-marking tyres	Tilt protection	Overload sensing system
Integrated hand shield	Automatic pothole guard	
Optional features		
Overhead anti-collision device	Headlight	RCBO
AC power to platform	Foot switch	

SINOBOOMTM

PARTNERS IN ACCESSTM

SINOBOOM.COM | SALES@SINOBOOM.COM

NO.128 EAST JINZHOU AV., NINGXIANG HI-TECH INDUSTRY PARK, CHANGSHA, HUNAN, CHINA, 410600

ELECTRIC SERIES SCISSOR LIFTS

0607SE(1932SE)

Compliance with ISO/CE/EAC standards

Model	0607SE(1932SE)	
Dimensions		
Max Working Height(Indoor/Outdoor)		7.6m/6.6m(24'11"/21'26")
A Max Platform Height(Indoor/Outdoor)		5.6 m/4.6m(18'5"/15')
B Max Horizontal Extension		0.6m(2')
C Length-Stowed		1.52m(4'12")
D Width-Stowed		0.81m(2'8")
E Height-stowed (Rail Folded)		1.77m(5'10")
E Height-stowed (Rail Unfolded)		2.1m(6'11")
E Height-stowed (Fixed Rail)		2.1m(6'11")
F Wheelbase		1.13m(3'9")
Ground Clearance(Pothole Guard Stowed)		0.065m(2.6")
Ground Clearance(Pothole Guard Deployed)		0.025m(0.98")
Platform Dimensions(L×W×H)		1.37m×0.7m×1.1m(4'6"×2'4"×3'7")
Performance		
Platform Allowable Occupants		2 persons(indoor) 1 person(outdoor)
Platform capacity		230kg(507lbs)
Lift Extension Capacity		120kg(265lbs)
Drive Speed-Stowed		4km/h(2.5mph)
Drive Speed-Raised		0.8km/h(0.5mph)
Lift Time(Unloaded)		26s
Descent Time(Unloaded)		24s
Gradeability		25%
Turning Radius(Inside/Outside)		0.45m/1.6m(1'6"/5'3")
Tilt Rating(Front to Back/Side to Side)		3°/1.5°
Tyre Size/Type		255×80mm (10×3.2")/solid
Weight		
Weight		1,210kg(2,668lbs)
Standards	ISO/CE/EAC	

